



US006997773B1

(12) **United States Patent**  
**Dubois et al.**

(10) **Patent No.:** **US 6,997,773 B1**  
(45) **Date of Patent:** **Feb. 14, 2006**

(54) **MOVEABLE TOY WITH CORRESPONDING AUDIO AND VISUAL OUTPUTS**

(75) Inventors: **David M. Dubois**, East Aurora, NY (US); **Albert Maggiore**, Lancaster, NY (US); **Marjorie D. Yoder-Parr**, Uniontown, OH (US)

(73) Assignee: **Mattel, Inc.**, El Segundo, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/347,511**

(22) Filed: **Jan. 21, 2003**

**Related U.S. Application Data**

(63) Continuation of application No. 10/143,803, filed on May 14, 2002, now abandoned.

(60) Provisional application No. 60/331,329, filed on May 16, 2001.

(51) **Int. Cl.**  
**A63H 30/00** (2006.01)

(52) **U.S. Cl.** ..... **446/175**; 446/272; 446/409

(58) **Field of Classification Search** ..... 446/175, 446/269, 272, 397, 409

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

78,361 A	5/1868	Clay
346,656 A	8/1886	Hopkins
942,610 A	12/1909	Bartholomae
1,707,826 A	4/1929	Tsobanacos
2,259,629 A	10/1941	Fisher
2,552,288 A	5/1951	Lee
2,624,127 A	1/1953	Okahara
2,820,327 A	1/1958	Charvat

2,940,755 A	6/1960	Pouder
3,346,968 A	10/1967	Dellinger
3,629,970 A	12/1971	Baynes et al.
3,763,734 A	10/1973	Meyer et al.
3,768,179 A	10/1973	Woodford et al.
3,902,256 A	9/1975	Liu
3,958,344 A	5/1976	Lesiak
3,982,764 A	9/1976	Dieball
4,184,286 A	1/1980	Spengler et al.
4,198,068 A	4/1980	Goldfarb et al.
4,280,809 A	7/1981	Greenberg et al.
4,291,489 A	9/1981	McCarthy, Jr.
4,295,294 A	10/1981	Rosenwinkel
4,432,159 A	2/1984	Kanno
4,445,297 A	5/1984	D'Andrade et al.
4,508,511 A	4/1985	McQueen
4,509,920 A	4/1985	Kaufmann
4,642,710 A	2/1987	Murtha et al.
4,693,697 A *	9/1987	Pagano ..... 446/272
4,729,564 A	3/1988	Kuna et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

FR 1416530 9/1964

**OTHER PUBLICATIONS**

Fisher-Price "Corn-Popper" from website. Downloaded Oct. 26, 2000, available at [www.fisher-pricestore.com](http://www.fisher-pricestore.com), one page.

*Primary Examiner*—Derris H. Banks


*Assistant Examiner*—Ali Abdelwahed

(74) *Attorney, Agent, or Firm*—Cooley Godward LLP

(57) **ABSTRACT**

A toy is provided having a motion detector that detects motion of the toy and generates a signal indicative of the motion. There is a visual display that is capable of selectively producing a visual output and an audio system capable of producing an audible output corresponding to, and descriptive of, the visual output.

**8 Claims, 17 Drawing Sheets**



# US 6,997,773 B1

Page 2

## U.S. PATENT DOCUMENTS

4,813,907 A *	3/1989	Rissman et al. ....	446/175	5,484,288 A	1/1996	DelGigante	
D302,186 S	7/1989	Klawitter		5,492,325 A	2/1996	Hawver	
4,915,633 A	4/1990	Auer et al.		5,538,430 A	7/1996	Smith et al.	
4,946,416 A	8/1990	Stern et al.		5,738,526 A	4/1998	Cerda et al.	
4,997,374 A	3/1991	Simone		5,913,683 A *	6/1999	Rahmoune et al. ....	434/104
5,011,451 A	4/1991	Holtier		5,931,338 A	8/1999	Hoeting et al.	
5,030,160 A	7/1991	Klawitter		D425,946 S	5/2000	Wei	
5,045,016 A	9/1991	Stern et al.		6,074,212 A	6/2000	Cogliano	
5,100,362 A	3/1992	Fogarty et al.		6,146,146 A	11/2000	Koby-Olson	
5,195,920 A *	3/1993	Collier .....	446/409	6,176,759 B1 *	1/2001	Trageser .....	446/272
5,209,695 A	5/1993	Rothschild		6,416,381 B1 *	7/2002	Walter et al. ....	446/397
D349,309 S	8/1994	Thornell		6,463,257 B1 *	10/2002	Wood .....	434/308
5,346,399 A	9/1994	Sakow		6,474,659 B1 *	11/2002	Horchler et al. ....	280/1.14
5,401,201 A	3/1995	Muraki		6,583,880 B1 *	6/2003	Berstis .....	356/407
5,407,216 A	4/1995	Liu		6,716,031 B1 *	4/2004	Wood et al. ....	434/159
5,411,429 A	5/1995	Klawitter		2002/0102908 A1 *	8/2002	Chan .....	446/269
5,429,513 A	7/1995	Diaz-Plaza		2003/0171063 A1 *	9/2003	Soto et al. ....	446/167
5,449,174 A	9/1995	Criner					
5,478,268 A *	12/1995	Au .....	446/227				

\* cited by examiner

FIG. 1




FIG. 2






FIG. 3



**FIG. 4**






FIG. 5

FIG. 6




FIG. 7






FIG. 8




FIG. 9




FIG. 10






FIG. 11








FIG. 13




FIG. 14





FIG. 15



FIG. 16



**FIG. 17**





FIG. 18



1

## MOVEABLE TOY WITH CORRESPONDING AUDIO AND VISUAL OUTPUTS

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation application of application Ser. No. 10/143,803 filed May 14, 2002, entitled "Moveable Toy with Corresponding Audio and Visual Outputs," now abandoned, which claims priority under 35 U.S.C. 119(e) to U.S. Provisional Application No. 60/331,329, filed May 16, 2001, the entire content of which is hereby incorporated by reference.

### BACKGROUND

#### 1. Field of the Invention

The present invention relates generally to toys, and more particularly, to toys with corresponding audio and visual outputs.

#### 2. Discussion of the Related Art

Toys that produce lights and sounds in various patterns have been provided. These toys appeal to young children, because they enjoy watching the lights and listening to the entertaining sounds. Conventional toys have primarily focused on the child's amusement.

A problem with conventional toys is that they tend to focus on entertaining the child while failing to promote the child's educational development such as vocabulary expansion or ability to recite the alphabet or series of numbers. Instead, these toys are primarily designed for one-dimensional use as amusement devices for small children. As the design of toys has progressed, however, parents, teachers, and other individuals involved in child-care have sought toys that provide a multifunctional yet economical approach to child development. Other toys, such as the category of educational learning toys, have provided educational or developmental stimuli, but have been static, immobile products that are less interesting to younger children.

Thus, there is a need for a children's toy that substantially obviates the limitations and disadvantages of conventional children's toys. Particularly, there is a need for an improved approach to the education of young children through a toy which incorporates visual or audible stimuli, such as corresponding lights and sounds that provide an educational experience for the child, while also incorporating movement into the play pattern of the toy to increase interest by the child user.

### SUMMARY OF THE INVENTION

The present invention solves the problems with, and overcomes the disadvantages of, conventional children's toys. In particular, the present invention relates to children's toys that produce audio and visual signals when the toy is moved along a support surface. The audio signals correspond to, and are descriptive of, the visual signals.

The invention includes a toy having a body that is adapted to be grasped by a user to propel the toy along a support surface. A motion detector coupled to the body detects motion of the body relative to the support surface and generates a signal indicative of the motion. There is a visual display that is capable of selectively producing a visual output and an audio system capable of selectively producing an audible output corresponding to the visual output. A controller is coupled to the detector, the visual display, and the audio system and is programmed to respond to receipt of

2

the motion indicating signal to cause the visual display to produce the visual output and the audio system to produce the corresponding audible output.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic illustration of a generic embodiment of a toy incorporating the principles of the present invention.

FIG. 2 is a further schematic illustration of the toy illustrated in FIG. 1.

FIG. 3 is a front perspective view of a first implementation of a toy embodying the principles of the present invention.

FIG. 4 is a bottom view of the toy illustrated in FIG. 3.

FIG. 5 is a cross-sectional view of the toy illustrated in FIG. 3 taken along the line 5—5 in FIG. 4.

FIG. 6 is a schematic illustration of the toy illustrated in FIG. 3.

FIG. 7 is a perspective view of a second implementation of a toy embodying the principles of the present invention.

FIG. 8 is a bottom view of the toy illustrated in FIG. 7.

FIG. 9 is a partial cut away view of the toy illustrated in FIG. 7.

FIG. 10 is a rear view of a component of the toy illustrated in FIG. 7.

FIG. 11 is a schematic illustration of the toy illustrated in FIG. 7.

FIG. 12 is a perspective view of a third implementation of a toy embodying the principles of the present invention.

FIG. 13 is a partial top view of the toy illustrated in FIG. 12.

FIG. 14 is a partial cross-sectional view of the toy illustrated in FIG. 12 taken along the line 14—14 in FIG. 13.

FIG. 15 is a detailed view of section 15 in FIG. 14.

FIG. 16 is a schematic illustration of the toy illustrated in FIG. 12.

FIG. 17 is a perspective view of a fourth implementation of a toy embodying the principles of the present invention.

FIG. 18 is a schematic illustration of the toy illustrated in FIG. 17.

### DETAILED DESCRIPTION

FIGS. 1 and 2 are schematic illustrations of a generic embodiment of a moveable toy **100** with corresponding audio and visual outputs. The toy **100** includes a body **110** that is adapted to be grasped by a user to propel the toy along a support surface **S**. The toy **100** can be either pushed or pulled by the user, but is configured such that it moves over the support surface **S**. A motion detector **120**, such as a momentary switch or an optical motion sensor, is coupled to the body **110** to detect motion of the body **110** relative to the support surface **S**. Upon detecting relative motion, the motion detector **120** generates a signal indicative of the motion. The signal generated by the motion detector **120** may simply be a signal indicative of motion in any direction. Optionally, the signal generated by the motion detector may indicate the fact that motion is taking place and may also indicate the direction of the motion. The motion detector **120** may take many forms, as will be described below in detail, provided that it is capable of detecting motion of the body **110** over the support surface.

A visual display **150** is coupled to the body **110** that is capable of selectively producing a visual output. The visual display **150** may be integrally coupled with the body **110** or removably coupled to the body **110**. Moreover, the visual display **150** may be mounted within an opening in the body

**110**, coupled externally to the body **110** or otherwise mounted such that the user readily views the visual display **150** when the toy **100** is in operation. The visual display **150** may be configured such that the user can view the visual display **150** while the body **110** is in motion as well as when the body **110** is at rest. Optionally, the visual display may be configured such that the user can only view the visual display **150** when the toy is at rest or only when the toy is in motion. The visual display **150** is that part of the toy **100** that presents the desirable visual image for the user to view.

An audio system **140** is included in the toy **100** that is capable of selectively producing an audible output corresponding to the visual output. The audio output corresponds to the visual output in the sense that the audio output is descriptive of the visual output, logically related to the visual output or both descriptive of and logically related to the visual output. For example, as will be described in detail below, if the visual output is a letter of the alphabet or a number, the audio output may be the spoken pronunciation of that displayed letter or number. The audible output can be any word or may be a particular tone or sequence of tones. The audible output may be produced and output simultaneously with the visual output. Optionally, the audible output may be produced and output before or after the visual output.

The relationship of various components of the toy **100** are schematically illustrated in FIG. 2. A controller **130** cooperates with the motion detector **120**, the visual display **150**, and the audio system **140** and is programmed to respond to receipt of the motion signal from the motion detector **120**. The controller may also be responsive to input from a user of the toy **100** via user input **160**. The controller **130** causes the visual display **150** to produce the visual output and similarly causes the audio system **140** to produce the corresponding audible output. The audio and visual outputs can be produced in a particular sequence or may be produced in a random manner provided the audible output corresponds to the visual output. The controller **130** can include memory or storage **130b** in which the audible and visual output information can be stored, logic **130a** (e.g., stored control software) that controls the operation of controller **130**, appropriate interfaces to the audio system **140** (e.g., speech synthesizer circuitry, audio amplifier, etc.) and visual display **150**.

Various physical implementations of this generic schematic description of the invention are described below. Corresponding reference numerals are used to reference structures in these implementations that correspond to the elements of the generic description above.

A first embodiment of the invention, representing a first physical implementation of the generic embodiment as described above, is illustrated in FIGS. 3–6 in which a toy **200** includes a body **210** that is supported by wheels or rollers **222** that are supported by an axle **224**. The body **210** may be in the form of a robot (as illustrated) or may be any other form that is entertaining to children. The toy **200** can be either pushed or pulled by the user, but is configured such that it translates over the support surface **S** on wheels **222**.

A motion detector **220** operates with the axle **224** to detect motion of the body **210** relative to the support surface **S**. The motion detector **220** includes an eccentric **226** mounted to the axle **224** and a switch **228** that is actuated by eccentric **226**. Eccentric **226** is a cam with a plurality of lobes that are able to actuate the switch **228**. As the wheels **222** roll over the support surface **S**, the axle **224** rotates, thereby rotating the eccentric **226**. As each lobe engages the normally open switch **228**, the switch closes, generating a signal detected

by controller **230**. The number of lobes on the eccentric **226** will determine how many times the switch **228** will be actuated per rotation of the wheels **222**. Optionally, a user of the toy **200** may spin the wheels **222** manually to activate the switch **228** instead of moving the toy **200** across the support surface.

A visual display **250** is mounted to the front face of the body **210** and is capable of selectively producing a visual output. In this embodiment, the visual display **250** is implemented as an array **254** of light emitting diodes (LEDs) **258** that are selectively activated to produce images on the visual display **250**. As will be appreciated, the visual display **250** for this embodiment of toy **200** may be implemented with other types of displays that are capable of producing various images from a matrix of pixels such as, for example, a Liquid Crystal Display (LCD).

Audio system **240** is included in the toy **200** that is capable of selectively producing an audible output corresponding to the visual output. The audio system **240** includes a speaker **244** mounted within the body **210** that is capable of emitting various sounds produced by the toy **200** as will be described in greater detail. The audio system **240** may also include a volume control **246** (switch SW4 in FIG. 6) that is moveable between a first position **V1** and a second position **V2**. When the volume control **246** is in the first position **V1**, the volume of the audio output is lower than when the volume control is in the second position **V2**. There may be multiple positions for the volume control to more selectively control the volume as known to those skilled in the art.

A controller **230** controls the output of sounds and lights from toy **200**. The controller **230** includes a controller logic that is stored in a memory of the controller **230**. The memory also stores the audio content and visual content that is ultimately output by the toy **200**. The controller **230** is configured to produce select audio and visual output in predetermined sequences according to the programming of the controller logic as would be apparent to those skilled in the art. Optionally, the controller **230** may be configured to produce the audio and visual output in a random fashion. An example of a controller that can be used in the present invention is the SPC251A that is available from Sunplus Technology Company, Ltd. Alternative processors or controllers may be utilized provided they are capable of producing corresponding audio and visual output as intended by the present invention.

The toy **200** includes user input **260** via which the user can provide input to effect the operation of toy **200**. User input **260** includes a mode selector **262** and an actuator **264**. Various modes of operation are alternatively selectable by mode selector **262** implemented as a switch (illustrated as SW1A in FIG. 6). In one mode of operation, when the switch SW1A is in a first position **P1**, controller **230** causes letters of the alphabet to be displayed on the visual display **250** by illuminating particular patterns of LEDs. The letters of the alphabet may be displayed sequentially or, optionally, may be displayed randomly. As each letter is displayed on the visual display **250**, the audio system **240** produces an audio output corresponding to the displayed letter, such as a spoken pronunciation of the letter. The display **250** and the audio output are activated when the switch **228** is actuated. The controller **230** causes the display **250** to change to a different letter of the alphabet each time the switch **228** is closed.

The toy **200** includes an actuator **264** that may be used to activate the display **250** and the audio system **240**. Actuator **264** is implemented as a large button atop the robot's "head",

5

which, when depressed by the user, closes a switch SW2 and sends a corresponding input signal to the controller 230. Each actuation of the actuator 264 causes the display of a subsequent letter of the alphabet as well as the spoken pronunciation of that displayed letter. Optionally, each actuation of the actuator 264 can cause the display of multiple letters and the corresponding spoken pronunciations of those displayed letters. Moreover, actuation of the actuator 264 may cause the audio system to produce a different output corresponding to the visual output, such as the spoken pronunciation of a word that begins with the displayed letter.

In an alternative mode of operation, with the mode switch SW1A in a second position P2, numbers may be displayed on the visual display 250 by illuminating particular patterns of LEDs. The numbers may be displayed sequentially or, optionally, may be displayed randomly. As each number is displayed on the visual display 250, the audio system 240 produces an audio output corresponding to the displayed number, such as a spoken pronunciation of the displayed number. The display 250 and the audio output are activated when the switch 228 is actuated. The controller 230 causes the display 250 to display a subsequent number each time the switch 228 is closed.

The actuator 264 may cause the display of subsequent numbers as well as the spoken pronunciation of the displayed number. Optionally, each actuation of the actuator 264 can cause the display of multiple numbers and the corresponding spoken pronunciations of the displayed numbers. Moreover, if the actuator 264 is actuated multiple times, the audio system 240 may be caused to produce an output such as a sequence of tones representing the displayed number. Similarly, the display 250 may illuminate individual LEDs each time a tone is played that represents the number that was previously displayed.

In a further mode of operation, shapes may be displayed on the visual display 250 by illuminating particular patterns of LEDs. The shapes may be displayed in a predetermined fashion or may be displayed randomly. As each shape is displayed on the visual display 250, the audio system 240 produces an audio output corresponding to the displayed shape such as a spoken pronunciation of the displayed shape. The display 250 and the audio output are activated when the switch 228 is actuated. The toy 200 can cycle through a different shape each time the switch 228 is closed. While the modes of operation may be selected by the user by changing the position of the mode switch 260, it is also possible for the toy 200 to randomly choose the mode of operation. Optionally, the mode of operation may be based on the speed or direction with which the toy 200 moves.

Using the toy 200, a child is provided with entertainment as well as the opportunity to learn letters, numbers and shapes.

The toy 200 may also include facial features 290 that can be illuminated such as by a bulb 292 when the audio system 240 produces an output to give the appearance that the toy 200 is speaking. Optionally, the facial features 290 may be moveable to give a more realistic appearance that the toy 200 is speaking.

The relationships among various components of the toy 200 are schematically illustrated in FIG. 6. The controller 230 cooperates with the motion detector switch 228, the LED array 254, and the audio system 240, and is programmed to respond to receipt of the motion signal from the motion detector switch 228 as described above. The controller 230 causes the visual display 250 to produce the visual output and similarly causes the audio system 240 to

6

produce the audible output that corresponds to, and is descriptive of, the image on the visual display. The audio and visual outputs can be produced in a particular sequence or may be produced in a random manner provided the audible output corresponds to the visual output.

The output of the visual display 250 may be dependent upon the position of the mode switch 260 as described above. With the mode switch SW1A in the first position P1, the controller 230 produces a display of letters on the LED array 254. With the mode switch in the second position P2, the controller 230 produces a display of numbers. When the mode switch is in the third position P3, the toy 200 is in the off position, and no power is delivered to the controller. More positions may be provided that would allow further modes of operation.

A second embodiment of the invention, representing a second physical implementation of the generic embodiment described above, is illustrated in FIGS. 7-11 in which the toy 300 includes a body 310 that is supported by wheels or rollers 322 that are supported by axles 324. The body 310 may be in the form of a train (as illustrated) or may be any other form that is entertaining to children. The toy 300 can be either pushed or pulled by the user, but is configured such that it translates over the support surface S on wheels 322.

A motion detector 320 operates with axle 324 to detect motion of the body 310 relative to the support surface S. The motion detector 320 includes an eccentric 326 mounted to the axle and a switch 328 actuated by eccentric 326. Eccentric 326 is a cam with a plurality of lobes that are able to actuate the switch 328. For example the eccentric may be oval, triangular, rectangular, or square in shape. As the wheels 322 roll over the support surface S, the axle 324 rotates, thereby rotating the eccentric 326. As each lobe engages the normally open switch 328, the switch closes, generating a signal detected by controller 330. The number of lobes on the eccentric 326 will determine how many times the switch 328 will be actuated per rotation of the wheels 322. Optionally, a user of the toy 300 may spin the wheels 322 manually to activate the switch 328 instead of rolling the toy 300 across the support surface.

A visual display 350 is coupled to the body 310 and is capable of selectively producing a visual output. In this embodiment, the visual display 350 is implemented as a string 354 of light emitting diodes (LEDs) 355, 356, 357 that are selectively activated. The LEDs 355, 356, 357 may be different colors. For example, there may be one or more red LEDs 355, one or more green LEDs 356, and one or more blue LEDs 357.

An audio system 340 is capable of selectively producing an audible output corresponding to, and descriptive of, the visual output. Audio system 340 includes a speaker 344 mounted within the body 310 that is capable of emitting various sounds produced by the toy 300 as will be described in greater detail.

A controller 330 controls the output of sounds and lights from toy 300. The controller 330 includes a controller logic that is stored in a memory of the controller 330. The memory also stores the audio content and visual content that is output by the toy 300. The controller 330 is configured to produce select audio and visual output in predetermined sequences according to the programming of the controller logic as would be apparent to those skilled in the art. Optionally, the controller 330 may be configured to produce the audio and visual output in a random fashion. An example of a controller that can be used in the present invention is the EMC 58200 that is available from Elan Microelectronics Corporation. Alternative processors or controllers may be utilized

provided they are capable of producing corresponding audio and visual output as intended by the present invention.

In one mode of operation of the toy **300**, as the toy **300** is moved across the support surface **S**, controller **330** causes the string **354** of LEDs of the visual display **350** to be illuminated in a predetermined sequence. Optionally, the LEDs of the string **354** are illuminated in a random fashion. A single LED is illuminated each time the switch **328** is actuated. Optionally, the entire series of LEDs is illuminated with each actuation of the switch **328**. Audio system **340** produces an output corresponding to the displayed color such as a spoken pronunciation of the color of the LED that is illuminated. For example, each time a red LED **355** is illuminated, the audio output **340** produces a spoken pronunciation of the word "RED." Similarly, each time a green LED **356** is illuminated, the audio output **340** produces a spoken pronunciation of the word "GREEN." Finally, each time a blue LED is illuminated, the audio output **340** produces a spoken pronunciation of the word "BLUE." In this manner, the child using the toy **300** is provided an entertaining experience as well as the opportunity to learn certain colors.

The toy **300** includes a user input **360** via which the user can provide input to effect the operation of toy **300**. User input **360** includes an actuator **364** that may be used to activate the display **350** and the audio system **340**. The actuator **364** is implemented as a button on the "stack" of the train, which when depressed by the user, closes a switch (illustrated as SW2 in FIG. **11**) and sends a corresponding input signal to controller **330**. Actuation of the actuator **364** causes the LEDs **355**, **356**, **357** to illuminate and causes the audio system to play a series of musical notes. Optionally, a single actuation of the actuator **364** may cause the LEDs **355**, **356**, **357** to illuminate in succession while the audio system **340** produces a spoken pronunciation of the color of each LED **355**, **356**, **357**. Moreover, actuation of the actuator **364** may cause the audio system **340** to produce a different output corresponding to the visual output such as the spoken pronunciation of the position of the illuminated LED with respect to the body of the train (i.e., front, middle, back).

The relationships among various components of the toy **300** are schematically illustrated in FIG. **11**. The controller **330** cooperates with the motion detector switch **328**, the visual display **350**, and the audio system **340**, and is programmed to respond to receipt of the motion signal from the motion detector switch **328**. The controller **330** causes the visual display **350** to produce the visual output and similarly causes the audio system **340** to produce the corresponding audible output. The audio and visual outputs can be produced in a particular sequence or may be produced in a random manner provided the audible output corresponds to the visual output.

A third embodiment of the invention, representing a third physical implementation of the generic embodiment described above is illustrated in FIGS. **12–15** in which a toy **400** includes a body **410** that is supported by wheels or rollers **422** that are supported by an axle **424**. The body **410** may be in the form of a conventional popper toy (as illustrated) or may be in another form that is appealing to children. The toy **400** can be either pushed or pulled by the user via the handle **412** and is configured such that it translates over the support surface **S** on wheels **422**.

A motion detector **420** operates with axle **424** to detect motion of the body **410** relative to the support surface **S**. The motion detector **420** includes an eccentric **426** that is mounted to axle **424** and triggers an actuator **458** and a switch **428**. Eccentric **426** is a cam with a plurality of lobes

that are able to trigger the actuator **458** and actuate the switch **428**. As the wheels **422** roll over the support surface **S**, the axle **424** rotates, thereby rotating the eccentric **426**. As each lobe engages actuator **458** and normally open switch **428**, the actuator **458** is triggered and the switch closes, generating a signal detected by controller **430**. The number of lobes on eccentric **426** will determine how many times the actuator will be triggered and how many times the switch **428** will be actuated per rotation of the wheels **422**. Optionally, a user of the toy **400** may spin the wheels **422** manually to actuate the switch **428** instead of rolling the toy **400** over the support surface.

A visual display **450** is coupled to the body **410** and is capable of selectively producing a visual output. In this embodiment, the visual display **450** is implemented as an enclosure **452** and objects **456** that are mobilized by the actuator **458**. When the actuator **458** is triggered, it is withdrawn and subsequently forced forward under the force of a spring (not shown). Once triggered, the actuator **458** causes the objects **456** within the enclosure to move randomly around the enclosure **452**. The visual display **450** may also include lights that are actuated by the switch **428**.

Each time the switch **428** is actuated, the controller **430** causes the audio system **440** to produce an audio output corresponding to the number of times the switch **428** has been actuated within a particular time frame such as a spoken pronunciation of the number of times the switch **428** has been actuated. The same number that is output by the audio system corresponds to the number of times that the actuator **458** has been triggered. The actuation of switch **428** and the triggering of the actuator **458** can be simultaneous or may be slightly delayed. In either case, the spoken pronunciation of the number of times the switch **428** has been triggered corresponds to the number of times the actuator **458** has been triggered or will be triggered. The toy **400** may be configured to only count up to a predetermined number. For example, the audio system **440** may only output the spoken pronunciation of numbers up to ten and then start over at number one.

In one embodiment, if the velocity of the toy **400** is less than a predetermined speed, the audio system **440** will perform as described above by outputting the spoken pronunciation of the number of times the switch **428** is actuated. In the event that the toy's velocity exceeds a predetermined velocity, the toy plays a series of musical notes. This is to eliminate speech counting and mechanical ball popping asynchronicity that may result at high velocities of the toy **400**.

The velocity of the toy **400** is measured by the number of actuations of switch **428**. Upon completion of either the current spoken pronunciation or musical note segment, if the velocity of toy **400** decreases below a predetermined threshold value (i.e., more than a predetermined time elapses without an actuation of switch **428**) the toy **400** enters a wait mode period for a predetermined amount of time. Should toy **400** then be restarted (i.e., there is an actuation of switch **428**) prior to the predetermined wait mode period expiration, the toy **400** will continue in the previous mode (counting or music) prior to the low velocity condition. Either a non-interruptible speech counting phrase or music segment will play on the next actuation of switch **428** from the zero velocity/stop condition contingent on the toy's previous mode at the zero velocity/stop condition. The velocity of toy **400** will again be re-measured during the playing of either the counting speech phrase or musical note segment and the next sequential numeric speech phrase or the next melody segment will play contingent on the velocity of toy **400**. If

the velocity of toy **400** remains at zero (i.e., there is no actuation of switch **428**) after the predetermined wait mode period expiration, the toy **400** will reduce power.

A controller **430** controls the output of sounds and lights emitted from toy **400**. The controller **430** includes a controller logic that is stored in a memory of the controller **430**. The memory also stores the audio content that is output by the toy **400**. The controller **430** is configured to produce select audio output in predetermined sequences according to the programming of the controller logic as would be apparent to those skilled in the art. Optionally, the controller **430** may be configured to produce the audio output in a random fashion. An example of a controller **430** that can be used in the present invention is the 58200 that is available from Elan Microelectronics Corporation. Alternative processors or controllers may be utilized provided they are capable of producing corresponding audio and visual output as intended by the present invention.

The relationships among various components of the toy **400** are schematically illustrated in FIG. 16. The controller **430** cooperates with the motion detector switch **428**, and the audio system **440**, and is programmed to respond to receipt of the motion signal from the motion detector switch **428**. The controller **430** causes the audio system **440** to produce the audible output corresponding to the number of times the actuator **458** is triggered. Note that in this embodiment the controller **430** does not control the visual display, but rather controls only the audio output in a manner synchronized with the visual display **450** which is driven by the user.

A fourth embodiment of the present invention, representing a fifth physical implementation of the generic embodiment described above is illustrated in FIG. 17 in which the toy **500** includes a body **510** in the shape of a ball having a first housing **512** and second housing **514** that are separated by a display surface **516**. The elements and operation of this embodiment are the same as the first embodiment with the following exceptions.

A visual display **550** is coupled to the display surface **516** such that it is viewable through the transparent second housing **514**. As will be appreciated, it is desirable for the body **510** to be weighted such that when it comes to a rest, the display **550** is viewable by the user of the toy **500**. A motion detector **520** is located within the first housing **512** and is configured to detect motion of the body **510** relative to the support surface S. The motion detector **520** provides a signal to a controller **530** to indicate that the toy **500** is in motion.

The visual display **550** is capable of selectively producing a visual output as described above. In this embodiment, visual display **550** is implemented as an array **554** of light emitting diodes (LEDs) **558** that are selectively activated to produce images on the visual display **550**. As will be appreciated, the visual display **550** for this embodiment of toy **500** may be implemented with other types of displays that are capable of producing various images such as, for example, a Liquid Crystal Display (LCD).

An audio system **540** is included in the toy **500** that is capable of selectively producing an audible output that corresponds to, and is descriptive of, the visual output as described above with reference to the first embodiment. Various components of the toy **500** are illustrated schematically in FIG. 18. The controller **530** controls the output of sounds and lights from toy **500** in the same manner described with respect to the first embodiment.

In one mode of operation, when the switch SW1A is in a first position P1, controller **530** causes letters of the alphabet to be displayed on the visual display **550** by illuminating

particular patterns of LEDs. The letters of the alphabet may be displayed sequentially or, optionally, may be displayed randomly. As each letter is displayed on the visual display **550**, the audio system **540** produces an audio output corresponding to the displayed letter, such as a spoken pronunciation of the letter. The display **550** and the audio output are activated when the body **510** comes to rest. When the body **510** comes to rest, the motion detector **520** indicates that there is no relative motion of the body **510** causing the controller **530** to activate the audio system **540** and the visual display **550**. The controller **530** causes the display **550** to cycle through the entire alphabet each time the body **510** comes to rest or may only display and recite a single letter each time the body **510** comes to rest. Optionally, the toy **500** may display a letter, output a spoken pronunciation of the displayed letter and also output a spoken pronunciation of a word that begins with the displayed letter each time the body **510** comes to a rest. When the body **510** is in motion, the audio system **540** may produce a series of musical notes to entertain the child before the body **510** comes to a rest.

In an alternative mode of operation, with switch SW1A is in a second position P2, numbers may be displayed on the visual display **550** by illuminating particular patterns of LEDs. The numbers may be displayed sequentially or, optionally, may be displayed randomly. As each number is displayed on the visual display **550**, the audio system **540** produces an audio output corresponding to the displayed number, such as a spoken pronunciation of the number. The display **550** and the audio output are activated when the body **510** comes to rest as described above. The controller **530** causes the display **550** to display a subsequent number each time the toy **500** comes to a rest.

In a further mode of operation, shapes may be displayed on the visual display **550** by illuminating particular patterns of LEDs. The shapes may be displayed in a predetermined pattern or may be displayed randomly. As each shape is displayed on the visual display **550**, the audio system **540** produces an audio output corresponding to the displayed shape such as a spoken pronunciation of the displayed shape. The display **550** and the audio output are activated as described above.

While particular, illustrative embodiments of the invention have been described, numerous variations and modifications exist that would not depart from the scope of the invention. For example, the features of the various embodiments may be combined in the several modes of operation of the toys described. For example, a toy may have an array of LEDs such as those described in the toys **200**, **500** that also include lights of various colors. Such a toy may produce a representation of a particular shape using only certain color lights. The audio system would then output a spoken pronunciation of the color as well as the shape. For example, if the visual display produced the image of a circle using blue LEDs, the corresponding audio output would be "BLUE CIRCLE." Additionally, the various displays could be combined in a single toy. In such an embodiment, the displays are alternatively selectable by switches or by different relative motions of the toy. For example, if the toy is moved forward across a support surface, a first display or mode would be activated. Likewise, if the toy is moved backward, a second display or mode would be activated. Moreover, instead of including LEDs as described above, any of the embodiments described may utilize light bulbs to produce the desired visual output.



Moreover, the display 350 of the toy 300 can illuminate LEDs in particular positions and the audio system 340 could produce a spoken pronunciation of the position of the LED (e.g., left, middle, right).

A toy having a display such as the displays 250, 550 could also provide a visual output of a word and a corresponding spoken pronunciation of the displayed word.

Instead of forming letters or numbers from arrays of lights, a graphical representation of a letter or number can be selectively illuminated, such as by a light. Thus, for example, in the third embodiment, the graphics on the handle (representing numbers from one to ten) could be selectively illuminated in synchronization with the audible output of the spoken pronunciation of the number.

The various features of the invention have been described in relation to children's educational toys. However, it will be appreciated that many of the features, such as the visual displays, the various body configurations, the audio outputs, and the motion detectors may be implemented on a variety of other children's products such as alternative toys, educational devices, infant support attachments, high chair attachments, stroller attachments, etc. Moreover, variations and modifications exist that would not depart from the scope of the invention. A number of these variations have been set forth above.

What is claimed is:

1. A toy, comprising:

- a body adapted to be grasped by a user to propel the toy along a support surface;
- a motion detector coupled to said body;
- said motion detector configured to detect motion of said body relative to the support surface and generate a signal indicating motion;
- a visual display configured to selectively produce a visual output including a light having a color;
- an audio system configured to selectively produce an audible output corresponding to said visual output and including a spoken pronunciation of said color; and
- a controller coupled to said detector, said visual display, and said audio system and programmed to respond to receipt of said signal to cause said visual display to produce said visual output and said audio system to produce said audible output.

2. The toy of claim 1, wherein said visual output is a first visual output and said audible output is a first audible output, said visual display is capable of selectively outputting a second visual output, said audio system is capable of selectively outputting a second audible output corresponding to said second visual output and said controller selectively causes said visual display to generate one of said first and

second visual outputs and said audio system to generate the corresponding one of said first and second audible outputs.

3. The toy of claim 2, further comprising an actuator configured to selectively actuate a third audible output.

4. The toy of claim 1, further comprising:

- a roller mounted on said body, said roller capable of supporting said body on the support surface and being rotatable in response to motion of said body with respect to the support surface, said motion detector configured to detect rotation of said roller.

5. The toy of claim 1, wherein said audible output is a first audible output and said signal is a first signal, said motion detector generating said first signal when said body is moved with respect to the support surface at a speed lower than a predetermined speed and generating a second signal when said body is moved with respect to the support surface at a speed greater than the predetermined speed, said controller responding to receipt of said second signal to cause said audio system to produce a second audible output.

6. A push toy, comprising:

- a body;
- a roller coupled to said body for rotation with respect to said body;
- a visual display including a first light having a first color and a second light having a second color, said visual display selectively displaying one of said first light having the first color and said second light having the second color in response to motion of said roller; and
- an audio generator including a first audible content including a spoken pronunciation of the first color and a second audible content including a spoken pronunciation of the second color, said audio generator selectively outputting one of said first audible content and said second audible content in response to motion of said roller.

7. The push toy of claim 6, wherein said roller includes a first wheel and a second wheel coupled by an axle.

8. A method of using a toy having a body, a roller, a visual display, and an audio generator, the method comprising:

- detecting rotation of the roller;
- causing the visual display to produce a visual output including a light having a color; and
- generating an audible output including a spoken pronunciation of the color, wherein as long as rotation of the roller is detected, the visual display will produce different visual outputs and audible outputs that correspond to each visual output will be generated.